

D-3000



4CH UHF Wireless



Introduction

D-3000 wireless conference microphone system is designed for simple economic conference application. With quick & easy installation, while providing reliable wireless connection & high-quality sound reproduction

Main Features

- Quick installation process with portable movement capability
- IR SYNC configuration
- 10 sets of system can work at a same venue meantime without interference
- Effective working distance: 60m

Features of Microphone Unit

- Hyper-cardioid directional capsule
- Anti-interference from mobile & 2.4G/5G devices
- OLED Display
- 8 hours battery life
- Detachable design

D-3000M Specification

| | |
|----------------------|------------------------|
| Carrier Frequency: | UHF620-850MHz |
| Modulation: | FM |
| No. of Channels: | 4 |
| Operation Distance: | 60m |
| Oscillation: | PLL |
| Sensitivity: | SNR>60dB @ 25KHz, 6dBv |
| Max Deviation Range: | ±45KHz |
| SNR: | >105dB |
| T.H.D: | <0.7%@1KHz |
| Frequency Response: | 45Hz-18KHz±3dB |
| Power supply: | DC12V~16V 10W |
| Output: | XLR, 6.3mm RCA |
| Weight: | 4.8kg |
| Dimension: | 421x200x45 mm |

D-3000D Specification

| | |
|----------------------|---------------|
| Carrier Frequency: | UHF620-850MHz |
| Oscillation: | PLL |
| Harmonic Radiation : | <-65dBm |
| Max Deviation Range: | ±45KHz |
| RF Power Output: | 15mW |
| Current Consumption: | <100mA |
| Battery Life: | 8 hours |
| Weight: | 0.5kg |
| Dimension: | 168x112x44 mm |