



FMX-IDV

The FMX-IDV is a DVI 1080P seamless input card with audio embedded signal for FMX system.

Port	1 x DVI (female DB24+5), 1 x Audio (3-pin pluggable terminal block)
Signal Standard	HDMI1.3 & HDCP Compliant
EDID	Supports EDID Management
Audio Format	PCM
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%
Power Consumption	4.5W



FMX-IHD

The FMX-IHD is a HDMI 1080P seamless input card with audio embedded signal for FMX system.

Port	1 x HDMI (female), 1 x Audio (3-pin pluggable terminal block)
Signal Standard	HDMI1.3 & HDCP Compliant
EDID	Supports EDID Management
Audio	PCM
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%
Power Consumption	5W



FMX-ISD

The FMX-ISD is a SDI 1080P seamless input card with 1 SDI loop out for FMX system. It supports 3G-SDI, HD-SDI & SDI.

Input	1 x SDI (female BNC)
Output	1 x SDI LOOP (female BNC)
Signal Standard	3G-SDI/HD-SDI/SDI
Output Resolution	1080P (max)
Transmission Distance	(1080P) ≤ 160m
Data Type	8 & 10 & 12bit
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%
Power Consumption	6.1W

Input Cards

FMX HD



FMX-ITP

The FMX-ITP is a HDBaseT 1080P seamless input card with audio de-embedded signal for FMX system. Paired with a transmitter for transmission of HDMI, IR, RS232, PoH up to 70m.

Port	1 x HDBT (RJ45), 1 x Audio (3-pin pluggable terminal block)
Signal Standard	HDMI1.3 & HDCP Compliant
EDID	Supports EDID Management
Audio	PCM
Transmission Distance	1080P ≤ 70m
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%
Power Consumption	13.5W



FMX-IVG

The FMX-IVG is a VGA 1080P seamless input card with audio embedded signal for FMX system. It is compatible with YPbPr, C-video & S-video.

Port	1 x VGA (female 15 pin HD), 1 x Audio (3-pin pluggable terminal block)
Signal Standard	VGA, CVBS, YPbPr
Output Resolution	VGA: 800x600, 1024x768, 720p, 1280x1024, 1080i, 1080P, 1920x1200 YPbPr: 720p, 1080i, 1080P
CVBS	6.75Gbps
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%
Power Consumption	4.6W