



MMX-40-DV

The MMX-40-DV is an DVI 1080P input card for MMX system.

Port	4 x DVI (female DB24+5/HDMI)
Signal Standard	HDMI 1.3 & HDCP Compliant
EDID	Supports EDID Management
Bandwidth	6.75 Gbps
Video signal	DVI-D full digital, HDMI
Audio Format	Embedded HDMI audio: PCM
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%



MMX-40-SD

The MMX-40-SD is a SDI output card for MMX system. it has 4 SDI outputs and each output has a loop output. It compatible with 3G-SDI, HD-SDI & SDI.

Port	4 SDI (Female BNC), 4 Loop (Female BNC); 0.8Vp-p ± 10%; 75Ω
Signal Type	SDI, HD-SDI, 3G-SDI
Transmission Distance	300m (Max.)
Maximum Data Rate	2.97Gbps, Auto Locked
Input Return Loss	<-14 dB@ 1 MHz ~ 1.5 GHz
Data Type	8bit, 10bit
Vedio Standards	SMPTE 292M, SMPTE 259M, SMPTE 424M, ITU-RBT.601, ITU-RBT.1120
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%



MMX-40-VG

The MMX-40-VG is an VGA output card with audio de-embedded signal for MMX system. It compatible with YPbPr, C-video & S-video.

Port	4 VGA, (Female 15 pin HD);
Output signal	RGBHV
Input Coupling	AC coupling only
Switching Type	Vertical interval
Resolution	1920x1080; XGA, 1024x768; 1280x720; WXGA, 1280x800
Bandwidth	350MHz (-3dB), fully load
Crosstalk	<-50dB@5MHz
Working Temperature	0 ~ +50°C
Relative Humidity	10% ~ 90%



MMX-40-BTS

The MMX-4I-BTS is an HDBaseT 4K SEAMLESS input card with audio de-embedded signal for MMX system.



MMX-40-UFS

The MMX-40-UFS is an Optical fiber SEAMLESS 4K output card for MMX system.



MMX-40-VS

The MMX-40-VS is an VGA SEAMLESS output card with audio de-embedded signal for MMX system.

MMX HD Output Cards