

SUH4T

SUH4T is a 4K HDBaseT splitter with 4 HDBaseT plus 1 HDMI outputs. It distributes HDMI signal via CAT cable at 230ft/70m with PoC, and enables IR and RS232 pass through to control the remote displays.



Input	1 HDMI(HDMI female), 1 RS232(3P captive screw connector), 1 IR(3.5mm mini jack)
Output	1 HDMI(HDMI female), 4 HDBaseT(RJ45), 1 RS232(3P captive screw connector), 1 IR(3.5mm mini jack), 1 IR LOOP(3.5mm mini jack), 1 RS232 LOOP(3P captive screw connector)
Bandwidth	10,2Gbps
Maximum Pixel Clock	340MHz
Transmission Distance	230ft/70m (max.)
Resolution	1080P, 3D & 4Kx2K
HDMI Standard	Supports HDMI 1.4 & HDCP
CMMR	>90dB@20Hz-20KHz
Frequency Response	20Hz-20KHz
Control	IR & RS232
Power Supply	24V DC;48W
Temperature	0 ~ +50°C
Humidity	10% ~ 90%
Chassis Dimension	W220 x H44 x D148(mm)



- Integrated with HDBaseT technology, 4K supported.
- 4 HDBaseT outputs with PoC at 230ft/70m.
- 1 HDMI output for local monitor or for cascading as 1x8 or bigger splitter.
- Addressable RS232 & Bi-directional IR to control display.
- Smart EDID management to avoid the display issue.
- LEDs for status checking.

