





Product Comparison

Technical Parameters	 Selected Product	 COMPARE	 COMPARE	Add product to compare
DS-D4415FI-CKF P1.53 Fine Fixel Pitch LED Display Unit	DS-D4418FI-CKF P1.86 Fine Fixel Pitch LED Display Unit	DS-D4425FI-CKF P2.5 Fine Fixel Pitch LED Display Unit		
Pixel Configuration	SMD 3-IN-1 LED	SMD 3-IN-1 LED	SMD 3-IN-1 LED	
Pixel Pitch Category	P1.53	P1.8	P2.5	
Pixel Pitch	1.538 mm	1.86 mm	2.5 mm	
Modules Component	3 × 2	3 × 2	3 × 2	
Dimensions (W × H × D)	640 mm × 480 mm × 69 mm (25.1 9" × 18.90" × 2.71")	640 mm × 480 mm × 69 mm (25.1 9" × 18.90" × 2.71")	640 mm × 480 mm × 69 mm (25.1 9" × 18.90" × 2.71")	
Resolution	416 × 312	344 × 258	256 × 192	
Area	0.3072 m ²	0.3072 m ²	0.3072 m ²	
Weight	8.8 kg (19.4 lb.)	8.8 kg (19.4 lb.)	8.8 kg (19.4 lb.)	
Pixel Density	422500 dots/m ²	288906 dots/m ²	160000 dots/m ²	
Lamp Board Housing	no housing	no housing	no housing	
Cabinet Material	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	
Maintenance Method	Front maintenance for all components	Front maintenance for all components	Front maintenance for all components	
Cabinet Flatness	0.1 mm	0.1 mm	0.1 mm	
Protection Level	Front protection level IP5X	Front protection level IP5X	Front protection level IP5x	
White Balance Brightness	600 cd/m ²	600 cd/m ²	600 cd/m ²	
Color Temperature	3000 K to 10000 K adjustable	3000 K to 10000 K adjustable	3000 K to 10000 K adjustable	
Viewing Angle	Horizontal 160°, vertical 160°	Horizontal 160°, vertical 160°	Horizontal 160°, vertical 160°	
Contrast Ratio	≥ 5000:1	≥ 5000:1	≥ 5000:1	
Color Uniformity	≤ ± 0.003Cx, Cy	≤ ± 0.003Cx, Cy	≤ ± 0.003Cx, Cy	
Brightness Uniformity	≥ 97%	≥ 97%	≥ 97%	
Gross Weight	45 kg (99.21 lb.)	45 kg (99.21 lb.)	45 kg (99.21 lb.)	
Package Dimension (W × H × D)	784 mm × 741 mm × 800 mm (30. 87" × 29.17" × 31.50") 4-in-1	784 mm × 741 mm × 800 mm (30. 87" × 29.17" × 31.50") 4-in-1	784 mm × 741 mm × 800 mm (30. 87" × 29.17" × 31.50") 4-in-1	
Lifespan	Lamp 100,000 hours	Lamp 100,000 hours	Lamp 100,000 hours	

Power Supply	200 to 240 VAC	200 to 240 VAC	200 to 240 VAC
Max. Consumption	≤ 600 W/m ²	≤ 600 W/m ²	≤ 600 W/m ²
Average Consumption	≤ 200 W/m ²	≤ 200 W/m ²	≤ 200 W/m ²
Driving Method	Constant current driving	Constant current driving	Constant current driving
Frame Frequency	60 Hz	60 Hz	60 Hz
Refresh Rate	3840 Hz	3840 Hz	3840 Hz
Grey Level	16 bit	16 bit	16 bit
Display Color	281 trillion	281 trillion	281 trillion
Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)	-10 °C to 40 °C (14 °F to 104 °F)	-10 °C to 40 °C (14 °F to 104 °F)
Working Humidity	10% to 80%RH	10% to 80%RH	10% to 80%RH
Storage Humidity	10% to 80%RH	10% to 80%RH	10% to 80%RH
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)	-20 °C to 60 °C (-4 °F to 140 °F)	-20 °C to 60 °C (-4 °F to 140 °F)

DS-D4415FI-CKF Full-Color LED Display



DS-D4415FI-CKF is the new generation small pixel pitch indoor full-color LED display. LED video wall features in seamlessness, high brightness/contrast, wide viewing angle, and accurate color restoration, achieving good visual effect. It is widely used in places such as monitoring center, command center, conference room, report hall, and exhibition hall.

- Displays position prompt of signal cable connection, convenient for quick connection of display unit and trouble shooting
- Acquires network statuses of receiving cards to help handle network communication problems
- Network loop backup improves product stability
- Dual-program backup enables the backup program of receiving cards for upgrade and restoration when exception occurs during program upgrading
- Loads parameters from the screen
- Low gray scale multiplication technology ensures more exquisite images




▪ Specification

Model		DS-D4415FI-CKF
Cabinet	Pixel Configuration	SMD 3-IN-1 LED
	Pixel Pitch Category	P1.53
	Pixel Pitch	1.538 mm
	Modules Component	3 × 2
	Dimensions (W × H × D)	640 mm × 480 mm × 69 mm (25.19" × 18.90" × 2.71")
	Resolution	416 × 312
	Area	0.3072 m ²
	Weight	8.8 kg (19.4 lb.)
	Pixel Density	422500 dots/m ²
	Lamp Board Housing	no housing
	Cabinet Material	Die-cast aluminum
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm
	Protection Level	Front protection level IP5X
Display	White Balance Brightness	600 cd/m ²
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx , Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	3840 Hz
	Grey Level	16 bit
	Display Color	281 trillion
Power	Power Supply	200 to 240 VAC
	Max. Consumption	≤ 600 W/m ²
	Average Consumption	≤ 200 W/m ²
Working Environment	Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
	Working Humidity	10% to 80%RH
	Storage Humidity	10% to 80%RH
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General	Gross Weight	45 kg (99.21 lb.)
	Package Dimension (W × H × D)	784 mm × 741 mm × 800 mm (30.87" × 29.17" × 31.50") 4-in-1
	Lifespan	Lamp 100,000 hours


▪ Available Model

DS-D4415FI-CKF

▪ Typical Application



Dimension



Unit: mm/inch

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
Info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-97-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com


Hikvision Korea
T +82-[0]31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com

DS-D4418FI-CKF Full-Color LED Display



DS-D4418FI-CKF is the new generation small pixel pitch indoor full-color LED display. LED video wall features in seamlessness, high brightness/contrast, wide viewing angle, and accurate color restoration, achieving good visual effect. It is widely used in places such as monitoring center, command center, conference room, report hall, and exhibition hall.

- Displays position prompt of signal cable connection, convenient for quick connection of display unit and trouble shooting
- Acquires network statuses of receiving cards to help handle network communication problems
- Network loop backup improves product stability
- Dual-program backup enables the backup program of receiving cards for upgrade and restoration when exception occurs during program upgrading
- Loads parameters from the screen
- Low gray scale multiplication technology ensures more exquisite images




▪ Specification

Model		DS-D4418FI-CKF
Cabinet	Pixel Configuration	SMD 3-IN-1 LED
	Pixel Pitch Category	P1.8
	Pixel Pitch	1.86 mm
	Modules Component	3 × 2
	Dimensions (W × H × D)	640 mm × 480 mm × 69 mm (25.19" × 18.90" × 2.71")
	Resolution	344 × 258
	Area	0.3072 m ²
	Weight	8.8 kg (19.4 lb.)
	Pixel Density	288906 dots/m ²
	Lamp Board Housing	no housing
	Cabinet Material	Die-cast aluminum
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm
	Protection Level	Front protection level IP5X
Display	White Balance Brightness	600 cd/m ²
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx , Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	3840 Hz
	Grey Level	16 bit
	Display Color	281 trillion
Power	Power Supply	200 to 240 VAC
	Max. Consumption	≤ 600 W/m ²
	Average Consumption	≤ 200 W/m ²
Working Environment	Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
	Working Humidity	10% to 80%RH
	Storage Humidity	10% to 80%RH
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General	Gross Weight	45 kg (99.21 lb.)
	Package Dimension (W × H × D)	784 mm × 741 mm × 800 mm (30.87" × 29.17" × 31.50") 4-in-1
	Lifespan	Lamp 100,000 hours


▪ **Available Model**

DS-D4418FI-CKF

▪ **Typical Application**



Dimension



Unit: mm/inch

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
Info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7852-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-97-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com


Hikvision Korea
T +82-[0]31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com

DS-D4425FI-CKF Full-Color LED Display



DS-D4425FI-CKF is the new generation small pixel pitch indoor full-color LED display. LED video wall features in seamlessness, high brightness/contrast, wide viewing angle, and accurate color restoration, achieving good visual effect. It is widely used in places such as monitoring center, command center, conference room, report hall, and exhibition hall.

- Displays position prompt of signal cable connection, convenient for quick connection of display unit and trouble shooting
- Acquires network statuses of receiving cards to help handle network communication problems
- Network loop backup improves product stability
- Dual-program backup enables the backup program of receiving cards for upgrade and restoration when exception occurs during program upgrading
- Loads parameters from the screen
- Low gray scale multiplication technology ensures more exquisite images




▪ Specification

Model		DS-D4425FI-CKF
Cabinet	Pixel Configuration	SMD 3-IN-1 LED
	Pixel Pitch Category	P2.5
	Pixel Pitch	2.5 mm
	Modules Component	3 × 2
	Dimensions (W × H × D)	640 mm × 480 mm × 69 mm (25.19" × 18.90" × 2.71")
	Resolution	256 × 192
	Area	0.3072 m ²
	Weight	8.8 kg (19.4 lb.)
	Pixel Density	160000 dots/m ²
	Lamp Board Housing	no housing
	Cabinet Material	Die-cast aluminum
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm
	Protection Level	Front protection level IP5x
Display	White Balance Brightness	600 cd/m ²
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx , Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	3840 Hz
	Grey Level	16 bit
	Display Color	281 trillion
Power	Power Supply	200 to 240 VAC
	Max. Consumption	≤ 600 W/m ²
	Average Consumption	≤ 200 W/m ²
Working Environment	Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
	Working Humidity	10% to 80%RH
	Storage Humidity	10% to 80%RH
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General	Gross Weight	45 kg (99.21 lb.)
	Package Dimension (W × H × D)	784 mm × 741 mm × 800 mm (30.87" × 29.17" × 31.50") 4-in-1
	Lifespan	Lamp 100,000 hours


▪ **Available Model**

DS-D4425FI-CKF

▪ **Typical Application**



Dimension



Unit: mm/inch

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
Info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7852-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-97-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-[0]31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com